

LIMIT 500

ELECTROMECHANICAL BARRIER FOR RESIDENTIAL, INDUSTRIAL OR PUBLIC USE





M COMUNELLO



in die-cast aluminium

Manual key and fold-away emergency

Robust steel frame with protective

treatment

release lever

Possibility to install a LED signal light on Possibility to install, along the beam length, beam strip LED for crossing-light version or with white light Robust ambidextrous beam support

0

Micro-switch and mechanical stop adjustment by one screw Easily accessible built-in control board for appropriate programming

Spherical self-lubricating eyelet-fixed spring for smoother, wear reducing

A single spring is provided which, depending on the length of the beam, is fixed to one of the holes in the spring tensioning arm





Depending on the length of the beam and relative accessories, the AC-541 spring must be fixed to one of the holes of the spring-tightening arm according to the table and diagram below.

SPRING POSITIONING AC-541					
ROD LENGTH	2 m	3 m	4 m	5 m	
EAM	1	1/2 🛊	1/2/3 *	2/3 *	
EAM WITH PROTECTIVE RUBBER AND LED STRIP LED	1	1/2 🛊	2/3 \star	3	
EAM WITH PROTECTIVE RUBBER, STRIP LED AND MOBILE SUPPORT	1	1/2 \star	3	3	
EAM WITH PROTECTIVE RUBBER, STRIP LED AND ALUMINUM SKIRT	-	2	3	-	
EAM WITH PROTECTIVE RUBBER, STRIP LED AND ALUMINUM SKIRT IND MOBILE SUPPORT	-	3	3	-	


* The SPRING can be fixed in the indicated holes with adequate adjustment for a correct balance of the rod. With the barrier unlocked, the rod must remain in balance at 45°



Every single product is duly tested at the end of each assembly line

TECHNICAL FEATURES

	LIMIT 500 24V
Power supply	230 VAC
Motor power supply	24 VDC
Power consumption	150 W
Current input	6,2 A
Torque	300 Nm
Duty cycle	Intensive use
Protection rating (IP)	IP44
Insulation class	2
Working temperature	-20°C/+50°C



For beams up to 5 m in length



For beams up to 10 m in length (5+5m)





OFFICIAL DEALER:



AUTOMATION FOR GATES, DOORS AND BARRIERS

FRATELLI COMUNELLO S.P.A.

HEADQUARTERS

Via Zarpellon, 33
36027 San Giuseppe di Cassola, Vicenza, Italy
Tel. +39 0424 585111 Fax +39 0424 533417
info@comunello.it www.comunello.com

REGISTERED OFFICE

Via Cassola,64 - C.P.79
36027 Rosà, Vicenza, Italy
Tel. +39 0424 585111 Fax +39 0424 533417
info@comunello.it www.comunello.com