LIMIT 800

COMUNELLO AUTOMATION

Elecromechanical 24V barrier raising systems with encoder for residential, public or industrial use
For entrances up to 8 m in width

24 VDC | ENCODER | DUAL KIT

LIMIT 800 — For entrances up to 8 m

SUITABLE FOR
INTENSIVE USE
(40%)

AVAILABLE MODELS:
HP | ONE TECHNOLOGY

AVAILABLE FINISHES:
Red | Black | Inox

ARTICLE	LIMIT 800 24V
Power supply	230 VAC
Operator power supply	24 VDC
Power consumption	150 W
Current input	6,2 A
Torque	300 Nm
Operating time	4 - 6 sec
Duty cycle	40%
Protection rating (IP)	IP44
Insulation class	2
Working temperature	-20°C / +50°C
Integrated control unit	CU 24V LT
Limit switch	Electromechanical
Encoder	Yes
Weight	95 kg

BAR ASSEMBLY AND SPRING CHOICE	LENGTH (METERS)				
	6,0	6,5	7,0	7,5	8,0
Bar	○	●	●	●	●
Bar with swing down support	●	●	●	●	●
Bar with joint	○	●	●	●	●

○ Medium spring AC 540 ● Double spring AC 550

COMUNELLO ®Copyright 2018 - All rights reserved